



BELLECRETE

BELLECRETE, INC.
449 Park Ave #B
San Fernando CA 91340-2525
T: 818 361 1832
E: bellecrete@gmail.com

MATERIAL PRODUCT DATA SHEET

Product:

Pool coping.

Style:

Modern.

Description:

The Modern Pool Coping has a 2" straight edge all around, with a ¼" bottom reveal.

Shapes:

Modern comprises straight, radius, radius end, corner.

Ingredients:

Pool Copings are crafted using a vibration process, employing super plasticizer, and cast with wet 5900 PSI hard rock concrete, utilizing Portland cement Type III.

Colors:

Pool Copings are available in eight colors: Custom White, White, Light Grey, Dark Grey, Midnight, Beige, Light Tan, Cream, Kahlua,

Sizes:

Modern 8"x24", 10"x24", 12x24, 18x24

Modern Jumbo: 14x32, 16x36

Technical Data:

Applicable standards – ASTM (American Society and Testing Materials)

C39/C231 – Concrete Compressive Strength

C150 – Standard Specification for Portland Cement

C642 – Water Absorption, Density, Voids in Hardened Concrete

Characteristics:

The weight of Modern Pool Coping is 27 pounds per square foot. Water absorption should not exceed an average of 6.0%, with no individual unit exceeding 7.0% for standard colors. Color may exhibit a slight shade variation, typically not exceeding 5%. Unit dimensions should not deviate more than +/- 1/8" from standard measurements, and no unit should differ by more than +/- 1/8" from approved samples. Test reports can be provided upon request. The concrete used is non-combustible.

Disclaimer:

Please note that precast concrete is subject to natural processes that may affect their appearance over time.

Color Dissolution: The color of concrete may fade when exposed to sunlight. This is a natural occurrence and should be expected with prolonged exposure.

Efflorescence: A crystalline deposit may develop on the surface of concrete products over time. This is a common phenomenon caused by natural reactions within the concrete and environmental factors.

Additional information available upon request.

September 2017